



Save as PDF



Peli protector cases - Total protection boxes - 1600 case



Interior dimensions:
54.4 x 41.9 x 20 cm (21" x 17" x 8")

Watertight, crushproof, and dust proof

- Open cell core with solid wall design - strong, light weight
- Automatic Pressure Equalization Valve
- O-ring seal
- Comfortable, rubber over-moulded handle
- Stainless steel hardware and padlock protectors
- 2 layer Pick 'N' Pluck™ foam with convoluted lid foam
- Personalised nameplate service available
- Unconditionally Guaranteed



Black Silver Yellow Orange Desert_tan

Peli protector cases - Total protection boxes - 1600 case SPECIFICATIONS

Exterior Dimensions (L x W x D)			Interior Dimensions (L x W x D)		
61.6 x 49.3 x 22 cm (24" x 19" x 9")			54.4 x 41.9 x 20 cm (21" x 17" x 8")		
Lid Depth	Bottom Depth	Total Depth			
4.4 cm (2")	15.5 cm (6.12")	20 cm (7.87")			
Lid Depth	Bottom Depth	Total Depth			
4.4 cm (1.75")	15.5 cm (6.12")	20 cm (7.87")			
Weight w/Foam	Weight w/o Foam	Buoyancy Max.			
6.4 kg. (14.11 lbs)	5.9kg (13 lbs.)	53.07 kg (117 lbs.)			
Range Temperature					
-40 / 99° C (-40 / 210° F)					

Personalized Nameplate Available

1600 Case Certificates

- IP67(1 meter submersion for 30 minutes)
- MIL C-4150J
- Def Stan 81-41/STANAG 4280
- ATA 300

Materials

Body	Latch	Lid O-Ring	Pins
Polypropylene	ABS	PolymerStainless Steel	
Foam	Purge Body	Purge Vent	Purge O-Ring
1.3 lb Polyurethane	ABS	3 Micron Hydrophobic Non-Woven PET	70 Shore Nitrile

Configuration

Cat. #	Description
1600	Peli protector cases - Total protection boxes - 1600 case

Peli protector cases - Total protection boxes - 1600 case Accessories

Cat. #	Description