



Overview

Model Name	Back UPS Pro BR 1300VA, 8 Outlets, AVR, LCD Interface
Includes	USB cable , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Afghanistan , Albania , Algeria , Andorra , Angola , Armenia , Australia , Austria , Azerbaijan , Bahrain , Bangladesh , Belarus , Belgium , Benin , Bhutan , Bosnia And Herzegovina , Botswana , Brunei Darussalam , Bulgaria , Burkina Faso , Burundi , Cambodia , Cameroon , Central African Republic , Chad , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Cook Islands , Cote D'Ivoire , Croatia , Cyprus , Czech Republic , Denmark , Djibouti , East Timor , Egypt , Equatorial Guinea , Eritrea , Estonia , Ethiopia , Fiji , Finland , France , Gabon , Gambia , Georgia , Germany , Ghana , Gibraltar , Greece , Guadeloupe , Guinea , French Guiana , Hong Kong , Hungary , Iceland , India , Indonesia , Iran (Islamic Republic Of) , Iraq , Ireland , Israel , Italy , Jordan , Kazakhstan , Kenya , KOREA, REPUBLIC OF , Kuwait , Latvia , Lebanon , Lesotho , Liberia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Madagascar , Malawi , Malaysia , Mali , Malta , Martinique , Mauritania , Mauritius , Mayotte , Moldova, Republic Of , Mongolia , Morocco , Mozambique , Myanmar , Namibia , Nepal , Netherlands , New Zealand , Niger , Nigeria , Norway , Oman , Pakistan , Papua New Guinea , Philippines , Poland , Portugal , Qatar , Reunion , Romania , Russian Federation , Rwanda , Saudi Arabia , Senegal , Sierra Leone , Singapore , Slovakia (Slovak Republic) , Slovenia , Somalia , South Africa , Spain , Sri Lanka , Sudan , Suriname , Sweden , Switzerland , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Thailand , Togo , Tunisia , Turkey , Turkmenistan , Turks And Caicos Islands , Uganda , Ukraine , United Arab Emirates , United States , Uzbekistan , Viet Nam , Western Sahara , Yemen , Zambia , Zimbabwe

Output

Output Power Capacity	780 Watts / 1300 VA
Max Configurable Power (Watts)	780 Watts / 1300 VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60 Hz +/-1 Hz
Output Frequency (sync to mains)	Line Interactive
Output Connections	(2) IEC 320 C13 (Surge Protection) , (6) IEC 320 C13 (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C14
Input voltage range for main operations	176 - 294 V

Maximum Input Current	10 A
Input Breaker Capacity	10 A

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	16 hour(s)
RBC Quantity	1

Communications & Management

Interface Port(s)	USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	509 Joules
Filtering	Full time multi-pole noise filtering :10% of IEEE surge let-through : zero clamping response time: instantaneous
Data Line Protection	RJ45 10/100/1000 Base-T Ethernet protection

Physical

Maximum Height	100.0 mm
Maximum Width	250.0 mm
Maximum Depth	382.0 mm
Net Weight	10.2 kg
Shipping Weight	11.85 kg
Shipping Height	330.0 mm
Shipping Width	485.0 mm
Shipping Depth	225.0 mm
Master Carton Units	1.0
Master Carton Weight	12.7 kg
Color	Black
SCC Codes	1073130434690 3

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.000 dB
Online Thermal Dissipation	21.500 BTU/hr

Conformance

Approvals	A-tick , C-tick , CE , EAC , GS Mark , RCM , TISI
Standard warranty	2 years repair or replace , 3 years repair or replace for European Union countries
Equipment protection policy	Lifetime : 150000 Euros , Lifetime : 200000 AUD , Lifetime : 75000 GBP

Sustainable Offer Status

RoHS	Compliant
------	-----------

