



APC Easy UPS BVX 1200VA, 230V, AVR, Schuko Sockets

BVX1200LI-GR

Call for More Information 0800 2799254

- Includes: User manual

Output

| | |
|---|-------------------------------------|
| Output power capacity | 650 Watts / 1.2kVA |
| Max Configurable Power (Watts) | 650 Watts / 1.2kVA |
| Nominal Output Voltage | 230V |
| Output Frequency (sync to mains) | 50/60 Hz +/- 1 Hz Sync to mains |
| Topology | Line interactive |
| Waveform type | Stepped approximation to a sinewave |
| Transfer Time | 6 ms typical : 10 ms maximum |

Input

| | |
|--|--------------------------------|
| Nominal Input Voltage | 230V |
| Input frequency | 50/60 Hz +/- 5 Hz Auto-sensing |
| Input Connections | Schuko |
| Cord Length | 1.2meters |
| Input voltage range for main operations | 140 - 300 (230 V) ACV |
| Number of Power Cords | 1 |
| Input Power Factor at Full Load | 0.54 |

Batteries & Runtime

| | |
|--------------------------------------|-------------------|
| Battery type | Lead-acid battery |
| Typical recharge time | 8hour(s) |
| Nominal Battery Voltage | 12 V |
| Expected Battery Life (years) | 2 - 3 |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Easy UPS BVX 1200VA, 230V, AVR, Schuko Sockets | BVX1200LI-GR | Downloaded on 02/25/2022 (EST)

| Batteries & Runtime | |
|--------------------------------|--|
| Battery Volt-Amp-Hour Capacity | 108 |
| Runtime | View Runtime Graph (Available in Technical Tab on site) |
| Efficiency | View Efficiency Graph (Available in Technical Tab on site) |

| Communications & Management | |
|-----------------------------|---|
| Control panel | LED Status display with on line : on battery |
| Audible Alarm | Alarm when on battery : distinctive low battery alarm |

| Surge Protection and Filtering | |
|--------------------------------|-----------|
| Surge energy rating | 273Joules |

| Physical | |
|-----------------|----------------|
| Maximum Height | 190MM, 19.0CM |
| Maximum Width | 140MM, 14.0CM |
| Maximum Depth | 390MM, 39.0CM |
| Net Weight | 7.5KG |
| Shipping weight | 8.5KG |
| Shipping Height | 297MM, 29.7CM |
| Shipping Width | 235MM, 23.5CM |
| Shipping Depth | 495MM, 49.5CM |
| Color | Black |
| SCC Codes | 10731304404603 |

| Environmental | |
|-----------------------------|---------------------------|
| Operating Temperature | 0 - 40 °C |
| Operating Relative Humidity | 0 - 95 (Non-condensing) % |
| Operating Elevation | 0 - 3000meters |
| Storage Temperature | -15 - 40 °C |
| Storage Relative Humidity | 0 - 95 (Non-condensing) % |
| Storage Elevation | 0 - 3000meters |

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Easy UPS BVX 1200VA, 230V, AVR, Schuko Sockets | BVX1200LI-GR | Downloaded on 02/25/2022 (EST)

Environmental

Audible noise at 1 meter from surface of unit 40.0dBA

Protection Class IP20

Conformance

Approvals CB , CE, EN/IEC 62040-1, EN/IEC 62040-2

Equipment protection policy Lifetime : 50000 euros

Standard warranty 2 years repair or replace

Sustainable Offer Status

RoHS Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.