



## APC Easy UPS BVX 2200VA, 230V, AVR, IEC Sockets

BVX2200LI

Call for More Information 0800 2799254

- Includes: User manual

Output	
Output power capacity	1.2kWatts / 2.2kVA
Max Configurable Power (Watts)	1.2kWatts / 2.2kVA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60 Hz +/- 1 Hz Sync to mains
Topology	Line interactive
Waveform type	Stepped approximation to a sinewave
Output Connections	(6) IEC 320 C19
Transfer Time	6 ms typical : 10 ms maximum

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 5 Hz Auto-sensing
Input Connections	IEC 60320 C20
Cord Length	1.2meters
Input voltage range for main operations	140 - 300 (230 V) ACV
Number of Power Cords	1
Input Power Factor at Full Load	0.54

Batteries & Runtime	
Battery type	Lead-acid battery
Typical recharge time	8hour(s)
Nominal Battery Voltage	24 V

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

APC Easy UPS BVX 2200VA, 230V, AVR, IEC Sockets | BVX2200LI | Downloaded on 02/25/2022 (EST)

Batteries & Runtime	
Expected Battery Life (years)	2 - 3
Battery Volt-Amp-Hour Capacity	216
Runtime	View Runtime Graph (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Control panel	LED Status display with on line : on battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm

Surge Protection and Filtering	
Surge energy rating	273Joules

Physical	
Maximum Height	190MM, 19.0CM
Maximum Width	140MM, 14.0CM
Maximum Depth	390MM, 39.0CM
Net Weight	12.2KG
Shipping weight	13.2KG
Shipping Height	297MM, 29.7CM
Shipping Width	235MM, 23.5CM
Shipping Depth	495MM, 49.5CM
Color	Black
SCC Codes	10731304404528

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 3000meters
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	0 - 95 (Non-condensing) %
Storage Elevation	0 - 3000meters

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

### Environmental

**Audible noise at 1 meter from surface of unit** 40.0dBA

**Protection Class** IP20

### Conformance

**Approvals** CB , CE, EN/IEC 62040-1, EN/IEC 62040-2

**Equipment protection policy** Lifetime : 50000 euros

**Standard warranty** 2 years repair or replace

### Sustainable Offer Status

**RoHS** Compliant

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.