



APC Smart-UPS 3000VA LCD RM 2U 230V with SmartConnect

SMT3000RMI2UC

- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
- Includes: CD with software, Documentation CD, Rack mounting hardware, Rack Mounting support rails, USB cable


Output	
Output power capacity	2.7kWatts / 3.0kVA
Max Configurable Power (Watts)	2.7kWatts / 3.0kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Topology	Line Interactive
Waveform type	Sine wave
Output Connections	(3) IEC Jumpers (Battery Backup) (8) IEC 320 C13 (Battery Backup) (1) IEC 320 C19 (Battery Backup)
Transfer Time	6ms typical : 10ms maximum

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	British BS1363A, IEC-320 C20, Schuko CEE 7/EU1-16P
Cord Length	1,83meters
Input voltage range for main operations	160 - 286V
Input voltage adjustable range for mains operation	151 - 302V
Number of Power Cords	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

Input	
Other Input Voltages	220, 240

Batteries & Runtime	
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3hour(s)
Replacement Battery	RBC43 
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	RJ-45 Serial, SmartSlot, USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering	
Surge energy rating	320Joules

Physical	
Maximum Height	86MM, 8.6CM
Maximum Width	480MM, 48.0CM
Maximum Depth	683MM, 68.3CM
Rack Height	2U
Net Weight	44.28KG
Shipping weight	51.7KG
Shipping Height	254MM, 25.4CM
Shipping Width	600MM, 60.0CM
Shipping Depth	980MM, 98.0CM
Units per Pallet	8.0

Technical Specifications

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	55.0dBA
Online thermal dissipation	348.0BTU/hr

Conformance	
Approvals	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Standard warranty	3 years repair or replace (excluding battery) and 2 year for battery

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs