



APC Smart-UPS SRT 1000VA RM 230V Network Card SRT1000RMXLI-NC

- High density, double-conversion on-line power protection with scalable runtime
- Includes: CD with software, Comms cable, Country-specific detachable power cord, Documentation CD, Installation guide, Network Management Card, Rack Mounting brackets, Rack mounting hardware, Rack Mounting support rails, Temperature Probe, USB cable, Warranty card

Output	
Output power capacity	1.0kWatts / 1.0kVA
Max Configurable Power (Watts)	1.0kWatts / 1.0kVA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 2%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double Conversion Online
Waveform type	Sine wave
Output Connections	(6) IEC 320 C13 (Battery Backup)
Bypass	Built-in Bypass

Input	
Nominal Input Voltage	230V
Input frequency	40 - 70 Hz (auto sensing)
Input Connections	British BS1363A, IEC-320 C14, Schuko CEE 7/EU1-16P
Cord Length	1,83meters
Input voltage range for main operations	50-150 (40% Load), 80 - 150V
Number of Power Cords	1

Batteries & Runtime	
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof

Technical Specifications

APC Smart-UPS SRT 1000VA RM 230V Network Card | SRT1000RMXLI-NC | Downloaded on 05/22/2019 (EST)

Batteries & Runtime	
Included Battery Modules	1
Typical recharge time	3hour(s)
Nominal Battery Voltage	48V
Expected Battery Life (years)	3 - 5
Extendable Run Time	1
Extended Run Options	APC-Smart-UPS-SRT-1000VA-RM-230V-Network-Card (Available in Technical Tab on site)
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	RJ-45 Serial, Smart-Slot, USB
Pre-Installed SmartSlot™ Cards	AP9631 (Available in Technical Tab on site)
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering	
Surge energy rating	432Joules

Physical	
Maximum Height	85MM, 8.5CM
Maximum Width	432MM, 43.2CM
Maximum Depth	505MM, 50.5CM
Rack Height	2U
Net Weight	21.0KG
Shipping weight	29.6KG
Shipping Height	246MM, 24.6CM
Shipping Width	594MM, 59.4CM
Shipping Depth	749MM, 74.9CM
Color	Black
Units per Pallet	12.0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-3000meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	50.0dBA
Online thermal dissipation	317.0BTU/hr
Protection Class	IP 20

Conformance	
Approvals	CE, EAC
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains SVHCs
Battery Directive	Compliant